


- Features :
  - 3000VDC I/O isolation
  - Internal SMD technology
  - Protection: Short circuit
  - Non-conductive plastic case
  - Cooling by free air convection
  - SMD package styles
  - 100% full load burn-in test
  - Low cost / High reliability
  - Approved: UL / CUL

## SPECIFICATION



MODEL NO.	F0505T-1W	F1205T-1W	F0509T-1W	F1209T-1W	F0512T-1W	F1212T-1W	F0515T-1W	F1215T-1W
ORDER NO.	SFT01L-05	SFT01M-05	SFT01L-09	SFT01M-09	SFT01L-12	SFT01M-12	SFT01L-15	SFT01M-15
OUTPUT	DC OUTPUT VOLTAGE		5V		9V		12V	
	OUTPUT CURRENT RANGE		0 ~ 200mA		0 ~ 111mA		0 ~ 84mA	
	EFFICIENCY		70%	70%	75%	73%	78%	73%
	RATED POWER		1W					
	RIPPLE & NOISE (max.) Note.2		100mVp-p					
	LINE REGULATION Note.3		±1.2% for 1% input variation					
	LOAD REGULATION Note.4		±8.0%					
	VOLTAGE TOLERANCE		±8.0%					
SWITCHING FREQUENCY(Typ.)		100KHz						
INPUT	VOLTAGE RANGE		4.5 ~ 5.5V	10.8 ~ 13.2V	4.5 ~ 5.5V	10.8 ~ 13.2V	4.5 ~ 5.5V	10.8 ~ 13.2V
	NORMAL VOLTAGE		5V	12V	5V	12V	5V	12V
	INPUT CURRENT	Full load	264mA	123mA	264mA	123mA	264mA	123mA
		No load	30mA	19mA	30mA	19mA	30mA	19mA
PROTECTION		Fuse recommended						
PROTECTION	OVERLOAD		Momentary		Protection type : Broken			
	SHORT CIRCUIT		Momentary		Protection type : Broken			
ENVIRONMENT	WORKING TEMP.		-40 ~ +85°C (Refer to output load derating curve)					
	WORKING HUMIDITY		20% ~ 90% RH non-condensing					
	STORAGE TEMP., HUMIDITY		-40 ~ +105°C, 10 ~ 95% RH					
	TEMP. COEFFICIENT		±0.03% / °C (0 ~ 50°C)					
VIBRATION		10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes						
SAFETY & EMC	SAFETY STANDARDS		UL60950-1, CSA C22.2					
	WITHSTAND VOLTAGE		I/P-O/P: 3KVDC					
	ISOLATION RESISTANCE		I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH					
OTHERS	MTBF		500khrs min. MIL-HDBK-217F(25°C)					
	DIMENSION		15.24*7.5*6.5mm or 0.6**0.295**0.24" inch (L*W*H)					
	WEIGHT		1.7g					


### Mechanical Specification




### Pin Configuration

Pin No.	Output
1	-Vin
2	+Vin
3	NC
5	-Vout
6	NC
7	NC
8	+Vout
10	NC
11	NC
12	NC

### Derating Curve



### Reflow Soldering Curve



### NOTE

1. All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
3. Line regulation is measured from low line to high line at rated load.
4. Load regulation is measured from 20% to 100% rated load.